

Risk Assessment in Life-Cycle Costing for Road Asset Management

Noppadol Piyatrapoomi, RMIT University
 Arun Kumar, RMIT University
 Neil Robertson, Queensland Department of Main Roads
 Justin Weligamage, Queensland Department of Main Roads



Background

- Australia has billions of dollars worth of civil infrastructure assets as roads, bridges, railways, buildings and other structures. Road assets alone are valued at around A\$ 140 billion.
- As condition of assets deteriorate over time, billions of dollars are spent annually in asset upkeep, which amounts to expenditure in the order of A\$27 million per day.
- Public demand for greater accountability in using public funds
- Need for risk management approaches that consider both financial and non-financial impacts




QLD Main Roads Road Asset Management

- Main Roads has stewardship of 34,000km of sealed road network in Queensland, Australia (value \$27b)
- Investment planning and asset management takes a medium to long term view: 10 to 20 years+
- Investment decision support relies on Comprehensive, relevant, quality asset data
 Investment modelling tools: agency and user impacts over asset life cycles
- Decision makers expect reliability in forecasting, investment risks understood



Research Tasks


- Task 1: The Development of a Procedure for Optimising Data Collection
- Task 2: Calibrating Pavement Prediction Models
- Task 3: The Development of a Method for Risk-Adjusted Assessment for life-cycle costing



Task 1: The Development of a Procedure for Optimising Data Collection

- Focus on strength testing of pavements – the most valuable, and also the most expensive data we collect on road pavements
- Studied probability distributions of subset of sample population of FWD data (200m interval)
- Interpretation of consequences of wider sample test intervals on the consistency of data population
- This method identified test intervals can be increased up to 1200m without much change in its characteristics





Task 2 – Calibrating Deterioration Prediction Models

- Adopted HDM4 deterioration model for predicting the rate of change in road pavement roughness developed by The International Study of Highway Development and Management (ISOHDM 2001)
- This study used the probability-based method and Monte Carlo simulation technique
- Measured roughness was modelled for 1400km length on Bruce Highway in Queensland


CRC Construction Innovation Queensland Government RMIT UNIVERSITY

HDM4 Model for Annual Rate of Change in Roughness

$$\Delta RI = K_{gp} (\Delta RI_s + \Delta RI_c + \Delta RI_r + \Delta RI_t) + m K_{gm} RI_a$$

K_{gp} = calibration factor, Default value = 1.0
 ΔRI = total change in roughness
 ΔRI_s = change in roughness due to pavement strength deterioration due to vehicles
 ΔRI_c = change in roughness due to cracking
 ΔRI_r = change in roughness due to rutting
 ΔRI_t = change in roughness due to pothole
 $(m K_{gm} RI_a = \Delta RI_e)$ = change in roughness due to climatic condition


CRC Construction Innovation Queensland Government RMIT UNIVERSITY




Task 3 – Risk Adjusted Assessment in Life-Cycle Costing

- Road investment tools can predict the life cycle costs for construction and maintenance road projects within a networks.
- Most inputs to such analysis are variable, and consequently the predicted life cycle cost is variable, and demonstrates a probability distribution.
- In this study, critical variable inputs are simulated, in order to assess the variability of the output costs.
- To demonstrate the methodology, only the variability of pavement strength was considered in the analysis.

CRC Construction Innovation Queensland Government RMIT UNIVERSITY





Conclusions

- Characterisation of the statistical properties of certain road asset data can be used to select an optimal test sampling plan, which is affordable and still statistically relevant.
 - will lower the cost of network level data collection
- Variability properties can be used for calibrating deterioration prediction models in predicting deterioration rates of road infrastructures to suit local conditions.
 - Model calibration is a major component of the investment analysis process and this unique stochastic method closely replicate the actual variability in network condition.

Logos for CRC Construction Innovation, Queensland Government, and RMIT UNIVERSITY are visible at the bottom of the slide.

Conclusions

- The risk-adjusted assessment in budget/cost estimates can be used in assessing the variability of budget/cost estimates arising from the variability and uncertainty of critical input variables.
 - will improve confidence in future affordability of investment decisions.

Logos for CRC Construction Innovation, Queensland Government, and RMIT UNIVERSITY are visible at the bottom of the slide.